



MiraFlor CR-N

Chemical Resistant Flooring

Care & Maintenance

Congratulations on choosing the finest quality chemical resistant flooring available. Your new Miracote MiraFlor CR-N Chemical Resistant Seamless Floor Covering System will provide years of trouble free service with a minimum of maintenance. Just follow the recommendations below to maximize the performance and life of your floor covering.

Cleaning

Cleaning your new Miracote floor is simple. Just wash with a mild solution such as "Simple Green" or "Ivory Liquid". Use a bristle brush to remove tough stubborn stains or residual compounds. Rinse thoroughly with clean water. Regular cleaning will prevent build-up of residue which can make the floor surface slippery when wet.

Maintenance

The Miracote MiraFlor CR-N Chemical Resistant Flooring incorporates Novolac epoxy technology which provides tighter crosslinking of the molecular structure of the polymeric resins base. The traffic topping is the only layer which requires ordinary maintenance.

The traffic topping is designated to withstand normal everyday wear and direct exposure to thermal and chemical elements. Harsh chemicals should be cleaned from the surface as soon as possible. Over a period of time the traffic topping needs to be resealed with Miracote MiraFlor CR Topcoat sealer. This is required when traffic patterns become visible in the flooring. This will be approximately 5 to 7 years in normal traffic areas and every 3 to 5 years in high traffic areas such as stairways and access corridors.

If your Miracote MiraFlor CR-N Flooring System becomes loose or debonded from the substrate for any reason, call the distributor, installing contractor or Miracote Immediately. Any problem with the flooring should be addressed immediately to prevent further damage.

Common Problems to Avoid

1. Do not expose floor to temperatures in excess of 300°.
2. Do not allow water migration through any protrusions in the flooring system
3. Avoid standing water by properly designing slope before application of the flooring system
4. Avoid heavy rolling loads with steel wheels
5. Floor areas subject to scratching by tracking of sand or grit from outside areas should be swept frequently



MIRACOTE PRODUCT LINE Crossfield Products Corp.

West Coast Office
3000 E. Harcourt Street
Rancho Dominguez, CA
90221
310-631-6594
310-886-9119 fax

East Coast Office
140 Valley Road
Roselle Park, NJ
07204
908-245-2808
908-245-0659 fax

www.miracote.com