



TENNIS COURT SURFACING

CARE & MAINTENANCE

Miracote Tennis Court Surfacing has been designed for long service with a minimum of maintenance. The following are recommendations for the routine cleaning and maintenance procedure which should be followed to keep a Miracote Tennis Court Surfacing installation in good condition.

CLEANING

Normal deposits of dirt and grime may be readily cleaned from a Miracote Tennis Court Surfacing installation by simply hosing or mopping with fresh water and scrubbing any hard-to-remove spots with a soft scrub brush. All wash water should be squeegeed or hosed to a drain.

Any ground-in grease spots should be scrubbed with a warm water and detergent solution.

SNOW REMOVAL

Miracote Tennis Court Surfacing can be damaged by gouging or scraping with sharp objects and should be protected against such damage; all snow removal should be accomplished using snow shovels which must be carefully handled to avoid damaging the roof. All shovels should be carefully inspected to insure that they have no sharp edges or breaks which might cause damage. Do NOT use ice choppers on Miracote Tennis Court Surfacing. The use of chloride-type ice and snow melting compounds will not damage Miracote Tennis Court Surfacing, although they may leave a white deposit which will require careful cleaning to remove.

FINISHING

After a period of years, it may be desirable to refinish Miracote Tennis Court Surfacing with the special Miracote colored dressing which is manufactured for this purpose. Refinishing will tend to renew the vividness of the color of the surface and will prolong the life of the tennis court. Miracote refinishing materials may be obtained through your Qualified Miracote Distributor.

REPAIR

Should your Miracote Tennis Court Surfacing installation be damaged, it can be repaired by a Qualified Miracote Contractor. In the event that any renovation or relocation of parts of the structure is planned, which will result in cutting or removal of portions of the Miracote Tennis Court Surfacing installation, you should contact a Qualified Miracote Distributor or Contractor before starting such work. Qualified Miracote Contractors will be in a position to recommend the best methods for repairing the installation.



MIRACOTE PRODUCT LINE Crossfield Products Corp.

West Coast Office
3000 E. Harcourt Street
Rancho Dominguez, CA
90221
310-631-6594
310-886-9119 fax

East Coast Office
140 Valley Road
Roselle Park, NJ
07204
908-245-2808
908-245-0659 fax

www.miracote.com