# MIRREDTE

# Miracote MPC Retarder

Product Technical Data Sheet

Miracote MPC Retarder is a single component additive that can be utilized to lengthen the working time of Miracote Protective Coating and MiraStamp. More specifically, the liquid is utilized in situations where the temperatures are above 85°F. The product adds valuable working time in conditions up to 95°F. It is not typically used under normal conditions up to (65 - 84°F),

as the cure time may lengthen. One bottle of the Miracote MPC Retarder is simply added to a 5gallon container of Miracote Paste.

This additive does not affect the performance of the fully cured final product.

#### **ADVANTAGES**

- Enable MPC or MiraStamp applications at temperatures above 85°F.
- Ease of incorporation.
- Assures normal working time under high temperature conditions.

#### **COVERAGE RATES**

600 sq. ft. per gallon/per coat

#### PACKAGING and COLORS

1-oz bottle

#### MIX RATIO

Add one vial to five gallons of Miracote MPC Liquid Catalyst or to five gallons of MiraStamp Liquid.

#### SHELF LIFE AND STORAGE

Shelf life will be one year from the date of manufacture as long as containers remain unopened and when material is store in a protected environment that is free from moisture, excessive heat and freezing temperatures, and direct sunlight.

#### WHERE TO USE

Use with Miracote MPC or MiraStamp.

#### TYPICAL PHYSICAL PROPERTIES @ 75°F (24°C)

State	Clear Liquid
Vehicle	1 year min., keep from freezing
Use Range	85 to 95°F

#### FOR BEST RESULTS

Install a minimum 4' by 4' test area site mock up for approval of acceptable color, texture, finish, adhesion, and any other critical requirement acceptable to the owner prior to proceeding with the installation.

Verify current versions of product technical data sheets (PTDS), material safety data sheets (MSDS), and installation guidelines (IG) at www.miracote.com.

Protect materials from excessive heat and cold and regularly check wet film thickness with mil gauge and monitor consumption to ensure correct application thicknesses and rate are obtained.

#### **OVERVIEW OF INSTALLATION STEPS**

• Once the five gallon container of Miracote Paste is open, pour in the Miracote MPC Retarder and mix for 1 minute. Then used as described in the Installation Guide for Miracote.



## Miracote Retarder

Product Technical Data Sheet

### PRODUCT AVAILABILITY

Crossfield Products Corp. Miracote maintains offices and factories at addresses listed below. Miracote products are available for purchase through reputable distribution in the building trades.

#### **MAINTENANCE**

For maximum sheen and cleanability, floor should be routinely treated with conventional maintenance finish followed by ordinary buffing.

#### SPECIFICATION ASSISTANCE

Consult Crossfield Products Corp. for specification assistance, detailing, etc. This consultation is highly recommended prior to specification.

#### **TESTING**

The technical data contained herein is the result of tests made in Crossfield's laboratories or in independent laboratories using small scale equipment, following generally accepted trade practices. Although this information is believed to be true and accurate, the use of different equipment for testing under dissimilar conditions or the testing of samples produced under dissimilar conditions may develop substantially different results.

#### LIMITED WARRANTY

NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICES ARE MET.

Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield's examination shall disclose to Crossfield's satisfaction to be thus defective.

IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD PRODUCT, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIAL NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.

CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.



Miracote Product Line Crossfield Products Corp

www.miracote.com

East Coast Office 140 Valley Road Roselle Park, NJ 07204 P: (908) 245-2808 F: (908) 245-0659 West Coast Office 3000 E. Harcourt Street Rancho Dominguez, CA 90221 P: (310) 631-6594 F: (310) 886-9119



MIR.170 MIRACOTE MPC RETARDER 12-10-2012