



CROSSFIELD PRODUCTS CORPORATION

www.crossfieldproducts.com

3000 E. Harcourt St.
Rancho Dominguez, CA 90221 (Headquarters)
(310)-886-9100 (8:00 AM – 5:00 PM Pacific Time)

140 Valley Rd.
Roselle Park, NJ 07204
(908)-245-2800 (8:00 AM – 5:00 PM Eastern Time)

SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

| | |
|--------------------------------------|---|
| <u>TRADE NAME (AS LABELED):</u> | MiraThane CRU Matte Part B |
| <u>CHEMICAL NAME/CLASS:</u> | Acrylic Emulsion |
| <u>PRODUCT USE:</u> | Specialty Resin ESD Floors |
| <u>SUPPLIER/MANUFACTURER'S NAME:</u> | Crossfield Products Corp. |
| <u>ADDRESS: (West Coast):</u> | 3000 E. Harcourt St. Rancho Dominguez, CA 90221 (Headquarters) |
| <u>ADDRESS: (East Coast):</u> | 140 Valley Rd. Roselle Park, NJ 07204 |
| <u>EMERGENCY PHONE:</u> | CHEMTREC: 800-424-9300 |
| <u>DATE OF PREPARATION:</u> | December 19, 2022 |
| <u>REVISION DATE:</u> | June 1, 2024 |

2. HAZARD(S) IDENTIFICATION



GHS Classification:

Skin Sensitization Cat. 1 : H317
Acute Toxicity Inhalation. Cat 4: H4332
Specific Target Organ Toxicity, Single Exposure, Inhalation, Cat 3: H335

Signal Word: (Warning)

Hazard Statements:

H317: May cause an allergic skin reaction
H332: Harmful if inhaled
H335: May cause respiratory irritation

Precautionary Statements:

P261: Avoid breathing dust/fume/gas/vapors/spray
P271: Use only outdoors or in a well-vented area
P272: Contaminate work clothing should not be allowed out of the workplace
P281: Use personal protective equipment
P285: In case of inadequate ventilation wear respiratory protection
P302+P352: IF ON SKIN: Wash with plenty of soap and water
P333+P313+P353: If skin irritation or rash occurs: Get medical attention: Take off contaminated clothing and wash it before reuse.
P304+P341+P311: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing: Call a POISEN CENTER or doctor/physician immediately
P404+P233: Store in a well-ventilated place. Keep container tightly closed.
P501: Recycle and or dispose of contents and containers in accordance with local, regional, national and international regulations.



3. COMPOSITION / INFORMATION ON INGREDIENTS

Table with columns: CHEMICAL NAME, CAS #, % w/w, and EXPOSURE LIMITS IN AIR (ACGIH, OSHA, IDLH, OTHER). Rows include Hydroprolic Hexamethylene diisocyanate oligomer and HDI (Hexamethylene diisocyanate).

NE = Not Established. C = Ceiling Limit. See Section 16 for Definitions of Terms Used.
NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-1993 format

4. FIRST-AID MEASURES

General information: Seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

SKIN EXPOSURE: For Skin contact, if available, wash with large amounts of running water and soap for 15 minutes. Remove contaminated clothing and shoes.

EYE EXPOSURE: For eye contact, immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water.

INHALATION: If inhaled, remove from area to fresh air. If not breathing, give artificial respiration.

INGESTION: Prevent aspiration of vomit. Turn victims head to the side. Never give anything by mouth to an unconscious person.


PERSONAL PROTECTION FOR FIRST-AID RESPONDERS: Use personal protective equipment. Wear self-contained breathing apparatus for firefighting if necessary.

5. FIRE-FIGHTING MEASURES

FLASH POINT, °C (method): 196°C (384.8°F) Closed Cup
AUTOIGNITION TEMPERATURE, °C: NE
FLAMMABLE LIMITS (in air by volume, %): Lower (LEL): NE Upper (UEL): NE

FIRE EXTINGUISHING MATERIALS:

Water Spray: YES Carbon Dioxide: YES
Foam: YES Dry Chemical: YES
Halon: YES Other: Any "ABC" Class.





MiraThane CRU Matte Part B

UNUSUAL FIRE AND EXPLOSION HAZARDS: Run-off from fire control may cause pollution. Keep fire-exposed containers cool with water spray to prevent rupture due to excessive heat. High pressure water hose may spread product from broken containers increasing contamination. If involved in a fire, this product may decompose to produce a variety of compounds (i.e. carbon monoxide, carbon dioxide, and other compounds). Emergency responders must wear the proper personal protective equipment suitable for the situation to which they are responding. Products of combustion are irritating to the respiratory tract and may cause breathing difficulty. Symptoms may be delayed several hours or longer depending upon the extent of exposure.

Explosion Sensitivity to Mechanical Impact: Not sensitive.

Explosion Sensitivity to Static Discharge: Not sensitive.

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural fire fighters must wear Self-Contained Breathing Apparatus and full protective equipment. Move fire-exposed containers, if it can be done without risk to firefighters. If possible, prevent run-off water from entering storm drains, bodies of water, or other environmentally sensitive areas. If necessary, discard or decontaminate fire response equipment before returning such equipment to service.

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel.

The proper personal protective equipment for incidental releases (e.g.-1 L of the product released in a well-ventilated area) use impermeable gloves, specific for the material handled, goggles, face shield, and appropriate body protection. In the event of a large release, use impermeable gloves, specific for the material handled, chemically resistant suit and boots, and hard-hat. Self Contained Breathing Apparatus or respirator may be required where engineering controls are not adequate or conditions for potential exposure exist. When respirators are required, Select NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance with latest OSHA and/or ANSI recommendations. Absorb spilled liquid with polypads or other suitable absorbent materials. Neutralize residue with sodium bicarbonate and water rinse. Decontaminate the area thoroughly. Test area with litmus paper to confirm neutralization. Place all spill residue in a suitable container. Dispose of in accordance with Federal, State, and local hazardous waste disposal regulations (see Section 13, Disposal Considerations).

7. HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash hands after handling this product. Do not eat or drink while handling this material. Remove contaminated clothing immediately. Discard contaminated clothing items, or launder before re-use. Inform anyone handling such contaminated laundry of the hazards associated with this product. Use ventilation and other engineering controls to minimize potential exposure to this product.

STORAGE AND HANDLING PRACTICES: All employees who handle this material should be trained to handle it safely. Avoid breathing mists or sprays generated by this product. Use in a well-ventilated location. **Keep from freezing.**

For Non-Bulk Containers: Open containers slowly, on a stable surface. Containers of this product must be properly labeled. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be stored in secondary containers, or in a diked area, as appropriate. Store containers away from incompatible chemicals. Keep container tightly closed when not in use. Wash thoroughly after using this material. Storage areas should be made of fire-resistant materials. If appropriate, post warning signs in storage and use areas. Inspect all incoming containers before storage, to ensure containers are properly labeled and not damaged. Empty containers may contain residual liquid, therefore, empty containers should be handled with care.



MiraThane CRU Matte Part B

Bulk Containers: All tanks and pipelines which contain this material must be labeled. Perform routine maintenance on tanks or pipelines which contain this product. Report all leaks immediately to the proper personnel.

Tank Car Shipments: Tank cars carrying this product should be loaded and unloaded in strict accordance with tank-car manufacturer's recommendation and all established on-site safety procedures. Appropriate personal protective equipment must be used (see Section 8, Engineering Controls and Personal Protective Equipment.). All loading and unloading equipment must be inspected, prior to each use. Loading and unloading operations must be attended, at all times. Tank cars must be grounded, level, brakes must be set or wheels must be locked or blocked prior to loading or unloading. Tank car (for loading) or storage tank (for unloading) must be verified to be correct for receiving this product and be properly prepared, prior to starting the transfer operations. Hoses must be verified to be clean and free of incompatible chemicals, prior to connection to the tank car or vessel. Valves and hoses must be verified to be in the correct positions, before starting transfer operations. A sample (if required) must be taken and verified (if required) prior to starting transfer operations. All lines must be blown-down and purged before disconnecting them from the tank car or vessel.

PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: Follow practices indicated in Section 6 (Accidental Release Measures). Make certain application equipment is locked and tagged-out safely. Always use this product in areas where adequate ventilation is provided. Decontaminate equipment before maintenance begins by a triple-rinse with water followed, if necessary, by using sodium bicarbonate and an additional rinse. Collect all rinsates and dispose of according to applicable Federal, State, or local procedures.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

VENTILATION AND ENGINEERING CONTROLS: If required use a corrosion-resistant ventilation system separate from other exhaust ventilation systems to ensure that there is no potential for overexposure to sprays, or mists of this product and that exposures are below those in section 2 (Composition and Information on Ingredients). Ensure eyewash/safety shower stations are available near areas where this product is used.

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below exposure limits listed in Section 2 (Composition and Information on Ingredients). If respiratory protection is needed, use only protection authorized in 29 CFR 1910.134, or applicable State regulations. If adequate ventilation is not available or if there is potential for airborne exposure above the exposure limits (listed in Section 2) a respirator may be worn up to respirator exposure limitations, check with respirator equipment manufactures recommendations/limitations. For a higher level of protection use positive pressure supplied air respiration protection or Self Contained Breathing Apparatus or if oxygen levels are below 19.5% or are unknown.

EMERGENCY OR PLANNED ENTRY INTO UNKNOWN CONCENTRATIONS OR IDLH CONDITIONS:

Positive pressure, full-facepiece Self Contained Breathing Apparatus; or positive pressure, full-facepiece Self Contained Breathing Apparatus with an auxiliary positive pressure Self Contained Breathing Apparatus.

EYE PROTECTION: Splash goggles or safety glasses. Face-shields are recommended when the operation can generate splashes, sprays or mists.

HAND PROTECTION: Wear appropriate gloves for routine industrial use. Use appropriate gloves for spill response, as stated in Section 6 of this SDS (Accidental Release Measures).

BODY PROTECTION: Use body protection appropriate for task. Cover-all, rubber aprons, or chemical protective clothing made from natural rubber are generally acceptable, depending upon the task.

**For Routine
Industrial
Applications**



Safety Glasses



Safety Gloves



9. PHYSICAL and CHEMICAL PROPERTIES

RELATIVE VAPOR DENSITY (air = 1): > ND
SPECIFIC GRAVITY (water = 1): 1.15
SOLUBILITY IN WATER: ND
VAPOR PRESSURE.: 17 hPa at 20°C (68°F) (approximate)
EVAPORATION RATE (n-BuAc=1): ND
MELTING/FREEZING POINT: -22°C (-7.6°F)
BOILING POINT: ≥300°C
pH: ND
ODOR: Faint Odor
LOG WATER/OIL DISTRIBUTION COEFFICIENT: ND

APPEARANCE AND COLOR: Liquid. Colorless to pale yellow.
HOW TO DETECT THIS SUBSTANCE (warning properties): ND

10. STABILITY and REACTIVITY

STABILITY: Stable.

DECOMPOSITION PRODUCTS: Thermal decomposition products of this solution can include a variety of compounds. (i.e. carbon monoxide, carbon dioxide, chlorine and other compounds).

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Acids, bases and electrolyte solution..

HAZARDOUS POLYMERIZATION: Will not occur by itself.

CONDITIONS TO AVOID: Avoid exposure or contact to incompatible chemicals.

11. TOXICOLOGICAL INFORMATION

11.2 Acute Toxicity Data

Skin corrosion I irritation

Application of 100 mg hexamethylene diisocyanate based isocyanurates caused moderate skin irritation in rabbits in a standard Draize test.

Application of 100 mg hexamethylene diisocyanate based isocyanurates caused moderate skin irritation in rabbits in a standard Draize test.

Slight eye irritation (rabbit); OECD Test Guideline 405. Application of 500 mg hexamethylene diisocyanate based isocyanurates caused moderate eye irritation in rabbits in a standard Draize test.

STOT (Specific Target Organ Toxicity) -Single exposure

Data for a similar HDI oligomer:

NOAEC for acute inhalation toxicity is 3.3 mg/m³, 6-hour exposure. May cause respiratory irritation based on evidence from animal tests.

Aspiration hazard

Data not available.

STOT (Specific Target Organ Toxicity) -Repeated exposure

Evidence for a similar substance: when inhaled and have caused concentration-related effects. In a 13-week study, increased wet lung weights, and inflammatory changes in the lungs were seen in rats at 25 mg/m³ and higher.

3-week inhalation NOAEL: 3.7 -4.3 mg/m³ (rat)

90-day inhalation NOAEL: 3.3 -3.4 mg/m³ (rat)

Sensitization -respiratory and/or skin

May cause an allergic skin reaction. HDI-based compounds showed skin sensitisation potential in a Local Lymph Node Assay. HDI-based isocyanurates caused slight to moderate skin sensitization in guinea pigs.



MiraThane CRU Matte Part B

Carcinogenicity

Data for a similar HDI oligomer:

Not classifiable as a human carcinogen. Did not show carcinogenic or mutagenic effects in animal experiments.

This material does not contain any component that is considered a human carcinogen by IARC (International Agency for Research on Cancer), ACGIH (American Conference of Governmental Industrial Hygienists), OSHA (Occupational Safety and Health Administration) or NTP (National Toxicology Program).

Reproductive toxicity

Data not available.

Germ cell mutagenicity

Data for a similar HDI oligomer:

In vitro: Negative in Ames test (Salmonella typhimurium with and without metabolic activation)

Interactive effects

Data not available.

12. ECOLOGICAL INFORMATION

1. Toxicity:

Data for a similar HDI oligomer: ••

Toxicity to fish: LC₅₀ > 100 mg/L Brachydanio rerio (96-hour)

Toxicity to crustacea: EC₅₀ > 100 mg/L Daphnia magna (48-hour)

Toxicity to aquatic plants: EC₅₀ > 1000 mg/L Scenedesmus sp. (72-hour)

Toxicity to microorganisms: EC₅₀ > 1000 mg/L Activated sludge microorganisms (3-hour)

2. Persistence and degradability:

Not readily biodegradable (1 %, 28 days).

3. Bioaccumulative potential:

Hydrolyses in presence of water. Bioaccumulation is unlikely.

4. Mobility in soil:

Hydrolyses to form water-insoluble compounds.



13. DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

Do NOT discard into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage.

Dispose of waste in accordance with relevant national, regional and local environmental control provisions.

14. TRANSPORTATION INFORMATION

Department of Transportation: Not regulated

IATA: Not regulated

IMDG: Not regulated

TDG: Not regulated

15. REGULATORY INFORMATION

US Federal Regulations

TSCA Section 12(b) export Notification (40 CFR 707, Subpt. D

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities

CERCLA Hazardous Substance List (40 CFR 302.4)

None present or none present in regulated quantities

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Respiratory or Skin Sensitization

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities

US EPCRA (SARA Title III) section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

SARA 311/312 Hazardous Chemical

Chemical Identity Threshold Planning Quantity

SARA 313 (TRI Reporting)

None present or none present in regulated quantities

Clean Air Act (CAA) section 112® Accidental Release Prevention (40 CFR 68.13):

None present or none present in regulated quantities

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities

STATE REGULATORY INFORMATION: Components of this product are covered under specific State regulations, as denoted below:

New Jersey Right-to-know: The following is required composition information: No listings

Pennsylvania Right-to-know: The following is required composition information: No listings

CALIFORNIA PROPOSITION 65: The components of this product listed below are known to the state of California to cause cancer, birth defects or other reproductive harm.

None listed

**16. OTHER INFORMATION**

PREPARED BY: ANDREW WATT

THIS INFORMATION IS DRAWN FROM RECOGNIZED SOURCES BELIEVED TO BE RELIABLE. CROSSFIELD PRODUCTS CORP. MAKES NO GUARANTEES NOR ASSUMES ANY LIABILITY IN CONNECTION WITH THIS INFORMATION. THE USER SHOULD BE AWARE OF CHANGING TECHNOLOGY, RESEARCH, REGULATIONS AND ANALYTICAL PROCEDURES THAT MAY REQUIRE CHANGES HEREIN. THE ABOVE DATA IS SUPPLIED UPON THE CONDITION THAT PERSONS WILL EVALUATE THIS INFORMATION AND THEN DETERMINE ITS SUITABILITY FOR THEIR USE.

DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these which are commonly used include the following:

CAS #: This is the Chemical Abstract Service Number which uniquely identifies each constituent. It is used for computer-related searching.

EXPOSURE LIMITS IN AIR:

ACGIH - American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits.

TLV - Threshold Limit Value - an airborne concentration of a substance which represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour **Time Weighted Average (TWA)**, the 15-minute **Short Term Exposure Limit**, and the instantaneous **Ceiling Level**. Skin adsorption effects must also be considered.

OSHA - U.S. Occupational Safety and Health Administration.

PEL - Permissible Exposure Limit - This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL," is placed next to the PEL which was vacated by Court Order.

IDLH - Immediately Dangerous to Life and Health - This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury. **The DFG - MAK** is the Republic of Germany's Maximum Exposure Level, similar to the U.S. PEL.

NIOSH is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (**OSHA**). NIOSH issues exposure guidelines called **Recommended Exposure Levels (RELs)**. When no exposure guidelines are established, an entry of **NE** is made for reference.

HMIS HAZARD RATINGS:

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: Health Hazard: **0** (minimal acute or chronic exposure hazard); **1** (slight acute or chronic exposure hazard); **2** (moderate acute or significant chronic exposure hazard); **3** (severe acute exposure hazard; onetime over-exposure can result in permanent injury and may be fatal); **4** (extreme acute exposure hazard; onetime over-exposure can be fatal). Flammability Hazard: **0** (minimal hazard); **1** (materials that require substantial pre-heating before burning); **2** (combustible liquid or solids; liquids with a flash point of 38-93°C [100-200°F]); **3** (Class IB and IC flammable liquids with flash points below 38°C [100°F]); **4** (Class IA flammable liquids with flash points below 23°C [73°F] and boiling points below 38°C [100°F]). Reactivity Hazard: **0** (normally stable); **1** (material that can become unstable at elevated temperatures or which can react slightly with water); **2** (materials that are unstable but do not detonate or which can react violently with water); **3** (materials that can detonate when initiated or which can react explosively with water); **4** (materials that can detonate at normal temperatures or pressures).

NATIONAL FIRE PROTECTION ASSOCIATION: Health Hazard: **0** (material that on exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials); **1** (materials that on exposure under fire conditions could cause irritation or minor residual injury); **2** (materials that on intense or continued exposure under fire conditions could cause temporary incapacitation or possible residual injury); **3** (materials that can on short exposure could cause serious temporary or residual injury); **4** (materials that under very short exposure could cause death or major residual injury). Flammability Hazard and Reactivity Hazard: Refer to definitions for "Hazardous Materials Identification System".

FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the **National Fire Protection Association (NFPA)**. Flash Point - Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. Autoignition Temperature: The minimum temperature required to initiate combustion in air with no other source of ignition. LEL - the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. UEL - the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

TOXICOLOGICAL INFORMATION:

Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are: **LD₅₀** - Lethal Dose (solids & liquids) which kills 50% of the exposed animals; **LC₅₀** - Lethal Concentration (gases) which kills 50% of the exposed animals; **ppm** - concentration expressed in parts of material per million parts of air or water; **mg/m³** - concentration expressed in weight of substance per volume of air; **mg/kg** - quantity of material, by weight, administered to a test subject, based on their body weight in kg. Data from several sources are used to evaluate the cancer-causing potential of the material. The sources are: **IARC** - the International Agency for Research on Cancer; **NTP** - the National Toxicology Program, **RTECS** - the Registry of Toxic Effects of Chemical Substances, **OSHA** and **CAL/OSHA**. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. Other measures of toxicity include **TDLo**, the lowest dose to cause a symptom and **TCLo** the lowest concentration to cause a symptom; **TDo**, **LDLo**, and **LDo**, or **TC**, **TCo**, **LCLo**, and **LCo**, the lowest dose (or concentration) to cause death. **BEI** - Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

REGULATORY INFORMATION:

This section explains the impact of various laws and regulations on the material. **EPA** is the U.S. Environmental Protection Agency. **WHMIS** is the Canadian Workplace Hazardous Materials Information System. **DOT** and **TC** are the U.S. Department of Transportation and the Transport Canada, respectively. Other acronyms used are: **Superfund Amendments and Reauthorization Act (SARA)**; the **Toxic Substance Control Act (TSCA)**; Marine Pollutant status according to the **DOT**; California's Safe Drinking Water Act (**Proposition 65**); the **Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA or Superfund)**; and various state regulations. This section also includes information on the precautionary warnings which appear on the materials package label.